



PETG Bypass

T5 LED SMD Tube

SUPERBRITE.



Americanlite® offer a premium quality UL-DLC LED Tubes can be widely used for various commercial and residential lighting applications, such as offices, shopping malls, parking lots, hotels, restaurants, hospitals, schools and many more.

- PET coated-glass housing
- G5 Base T6 Tube
- 70% energy savings compared to traditional fluorescent tubes
- Environment friendly, no mercury or any other hazardous materials
- Powered on one end
- Complies with NSF-2 Standard (safe for food industry)
- **For double end power add "B" at end of part #**

• **Does not work with ballast**

Ordering information

Model	W	Base	CCT	Input Voltage	Lumens	Diffuser	Length
AL571327	9w	G5	3000K	120-277V	1100lm	Opal	563mm
AL571328			4000K	120-277V	1100lm	Opal	563mm
AL571329			5000K	120-277V	1200lm	Opal	563mm
AL571330			6500K	120-277V	1200lm	Opal	563mm
AL571280	13w	G5	3000K	120-277V	1600lm	Opal	1163mm
AL571281			4000K	120-277V	1650lm	Opal	1163mm
AL571282			5000K	120-277V	1650lm	Opal	1163mm
AL571283			6500K	120-277V	1700lm	Opal	1163mm
AL571284	16w	G5	3000K	120-277V	2150lm	Opal	1163mm
AL571285			4000K	120-277V	2200lm	Opal	1163mm
AL571286			5000K	120-277V	2200lm	Opal	1163mm
AL571287			6500K	120-277V	2300lm	Opal	1163mm
AL571288	25w	G5	3000K	120-277V	3200lm	Opal	1163mm
AL571289			4000K	120-277V	3300lm	Opal	1163mm
AL571290			5000K	120-277V	3300lm	Opal	1163mm
AL571291			6500K	120-277V	3400lm	Opal	1163mm

- Notes:
- No DLC for 6500K
 - Lumen tolerance up to 7%
 - Length of tube with pin

Packing information

Color Sleeve packing

Model	CBM per master	Pieces per master	Box Dimensions (cm)	Gross weight (Kg)
9w	0.0127	25	65 x 14 x 14	4.5
13w / 16w / 25w	0.0216	25	122.3 x 13.3 x 13.3	7.5